

ViewSonic® LCD DISPLAY **VX2776-smh**

Key Features

- SuperClear® IPS panel for vivid picture quality and wider viewing angles
- Frameless bezel and stylish stand
- 100Hz Refresh Rate delivers fluid visuals
- Flexible connectivity with VGA and two HDMI ports
- User-customized and pre-calibrated ViewMode for every scenario



Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2776-SMH is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless experience ideal for multi-monitor setups. The Full HD resolution boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. The Built-in HDMI and VGA deliver flexible connectivity options for a wide range of devices.

Visit Us www.viewsonic.com

DISPLAY	
Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,300:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 100% size (Typ)
Pixel Size:	0.311 mm (H) x 0.311 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)
COMPATIBILITY	
PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080
CONNECTOR	
VGA:	1
3.5mm Audio In:	1
3.5mm Audio Out:	1
HDMI 1.4:	2
Power in:	3-pin Socket (IEC C14 / CEE22)
AUDIO	
Internal Speakers:	2Watts x2
POWER	
Eco Mode (Conserve):	18W
Eco Mode (optimized):	21W
Consumption (typical):	24W
Consumption (max):	25W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply
ADDITIONAL HARDWARE	
Kensington Lock Slot:	1

CONTROLS	
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
OPERATING CONDITIONS	
Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%
WALL MOUNT	
VESA Compatible:	75 x 75 mm
INPUT SIGNAL	
Frequency Horizontal:	RGB Analog: 15 ~ 83KHz, HDMI (v1.4): 30 ~ 115KHz
Frequency Vertical:	RGB Analog: 50 ~ 75Hz, HDMI (v1.4): 50 ~ 100Hz
VIDEO INPUT	
Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog
ERGONOMICS	
Tilt (Forward/Back):	-3° / 15°
WEIGHT (IMPERIAL)	
Net (lbs):	8.8
Net Without Stand (lbs):	7.9
Gross (lbs):	12.1
WEIGHT (METRIC)	
Net (kg):	4
Net Without Stand (kg):	3.6
Gross (kg):	5.5
DIMENSIONS (IMPERIAL) (WXHxD)	
Packaging (in.):	27.6 x 18.2 x 4.4
Physical (in.):	24.2 x 17.5 x 7.2
Physical Without Stand (in.):	24.2 x 14.1 x 1.9
DIMENSIONS (METRIC) (WXHxD)	
Packaging (mm):	702 x 462 x 112
Physical (mm):	614 x 443 x 184
Physical Without Stand (mm):	614 x 357 x 49
GENERAL	
Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, BIS
PACKAGE CONTENTS:	VX2776-SMH x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick S Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market