


serie TER

Repartidores inductivos blindados Inductively Shielded Splitters Répartiteurs inductifs blindés

5-1000 MHz
5-1000 MHz
5-1000 MHz



TER 4

Código
Code 0970004
Code

Banda cubierta (MHz)
Covered Band (MHz) 5-1000
Bande de fréquence (MHz)

Banda de retorno (MHz)
Return path Band (MHz) 5-30 / 5-65
Bande de retour (MHz)

Nº de salidas
Nr. of outputs 4
Nb de sorties

	Freq. (MHz)	TYP	MAX
Atenuación de distribución (dB)	5-300	6,1	6,9
Distribution attenuation (dB)	300-606	6,2	7,0
Atténuation de distribution (dB)	606-1000	7,8	8,5

Desacoplo entre salidas (dB)	5-300	>35
Decoupl. between outputs (dB)	300-606	>25
Désaccoup. entre sorties (dB)	606-1000	>25

Pérdidas de retorno (dB)		
Return loss (dB)	IN	>18
Pertes de retour (dB)	OUT	>18

Factor de apantallamiento (dB)		
Screening factor (dB)	>100	
Facteur d'accouplement (dB)		

Impedancia (W)		
Impedance (W)	75	
Impédance (W)		

Paso de corriente		
Current pass	no	
Passage de courant		


Conectores	F hembra	
Connectors	F female	
Connecteurs	F femelle	

Soporte plástico montaje	Incluido	
Plastic support	Included	
Support plastique pour le montage	Inclu	

Dimensiones (mm)		
Dimensions (mm)	10 pcs: 165 x 165 x 70	
Dimensions (mm)	120 pcs: 330 x 330 x 210	

Peso embalaje (Kg)		
Packing weight (Kg)	10 pcs: 1	
Poids du l'emballage (Kg)	120 pcs: 12	

Cantidad por embalaje		
Packing quantity	10 / 120	
Quantité par emballage		



TER 6

Código
Code 0970006
Code

Banda cubierta (MHz)
Covered Band (MHz) 5-1000
Bande de fréquence (MHz)

Banda de retorno (MHz)
Return path Band (MHz) 5-30 / 5-65
Bande de retour (MHz)

Nº de salidas
Nr. of outputs 6
Nb de sorties

	Freq. (MHz)	TYP	MAX
Atenuación de distribución (dB)	5-300	9,3	10,3
Distribution attenuation (dB)	300-606	9,5	10,5
Atténuation de distribution (dB)	606-1000	10,0	11,0

Desacoplo entre salidas (dB)	5-300	>35
Decoupl. between outputs (dB)	300-606	>25
Désaccoup. entre sorties (dB)	606-1000	>25

Pérdidas de retorno (dB)		
Return loss (dB)	IN	>18
Pertes de retour (dB)	OUT	>18

Factor de apantallamiento (dB)		
Screening factor (dB)	>100	
Facteur d'accouplement (dB)		

Impedancia (W)		
Impedance (W)	75	
Impédance (W)		

Paso de corriente		
Current pass	no	
Passage de courant		


Conectores	F hembra	
Connectors	F female	
Connecteurs	F femelle	

Soporte plástico montaje	Incluido	
Plastic support	Included	
Support plastique pour le montage	Inclu	

Dimensiones (mm)		
Dimensions (mm)	5 pcs: 165 x 125 x 70	
Dimensions (mm)	60 pcs: 330 x 250 x 210	

Peso embalaje (Kg)		
Packing weight (Kg)	5 pcs: 0.9	
Poids du l'emballage (Kg)	60 pcs: 11	

Cantidad por embalaje		
Packing quantity	5 / 60	
Quantité par emballage		



TER 8

Código
Code 0970008
Code

Banda cubierta (MHz)
Covered Band (MHz) 5-1000
Bande de fréquence (MHz)

Banda de retorno (MHz)
Return path Band (MHz) 5-30 / 5-65
Bande de retour (MHz)

Nº de salidas
Nr. of outputs 8
Nb de sorties

	Freq. (MHz)	TYP	MAX
Atenuación de distribución (dB)	5-300	9,7	10,3
Distribution attenuation (dB)	300-606	10,0	10,5
Atténuation de distribution (dB)	606-1000	11,0	12,5

Desacoplo entre salidas (dB)	5-300	>35
Decoupl. between outputs (dB)	300-606	>25
Désaccoup. entre sorties (dB)	606-1000	>25

Pérdidas de retorno (dB)		
Return loss (dB)	IN	>18
Pertes de retour (dB)	OUT	>18

Factor de apantallamiento (dB)		
Screening factor (dB)	>100	
Facteur d'accouplement (dB)		

Impedancia (W)		
Impedance (W)	75	
Impédance (W)		

Paso de corriente		
Current pass	no	
Passage de courant		

Conectores	F hembra	
Connectors	F female	
Connecteurs	F femelle	

Soporte plástico montaje	Incluido	
Plastic support	Included	
Support plastique pour le montage	Inclu	

Dimensiones (mm)		
Dimensions (mm)	5 pcs: 165 x 125 x 70	
Dimensions (mm)	60 pcs: 330 x 250 x 210	

Peso embalaje (Kg)		
Packing weight (Kg)	5 pcs: 0.9	
Poids du l'emballage (Kg)	60 pcs: 11	

Cantidad por embalaje		
Packing quantity	5 / 60	
Quantité par emballage		

