

Hardware	
host connector	USB-C® with DisplayPort™ Alt-mode
infrared	N/A
led indicators	N/A
ports	N/A
power source	USB™ Type-A male
warranty	1 Year Limited
Performance	
audio channel	2.1 via HDMI™
esd protection	N/A
hdcp compliance	HDCP 1.4
hdmi compliance	HDMI™ v1.3
infrared return frequency	N/A
ovp protection	

N/A

rf output power

N/A

security - encryption

WPA2

supported resolution - output

1920 × 1080

1280 × 720

Physical Specifications

cable length

USB-C® Transmitter (TX): 3.34 in. (85 mm)

HDMI™ Receiver (RX): 23.6 in. (600 mm)

color

White

enclosure type

White

operating humidity

< 85% non-condensing

operating temperature

+14 to +104°F (-10 to +40°C)

product depth

USB-C® Transmitter (TX): 0.66 in. (17 mm)

HDMI™ Receiver (RX): 0.41 in. (10.5 mm)

product height

USB-C® Transmitter (TX): 2.56 in. (65 mm)

HDMI™ Receiver (RX): 2.2 in. (57 mm)

product weight

USB-C® Transmitter (TX): 1.9 oz (54g)

HDMI™ Receiver (RX): 1.11 oz (31.5g)

product width

USB-C® Transmitter (TX): 2.56 in. (65 mm)

HDMI™ Receiver (RX): 0.95 in. (24 mm)

storage humidity

< 85% non-condensing

storage temperature

-4 to +122°F (-20 to +50°C)

Wireless Protocols

antenna type: Internal antenna

channel width: 20 MHz, 40 MHz

Frequency: 2.4 GHz, 5 GHz

Range: Up to 10 – 15 meters

Standard: IEEE 802.11ac

Package Contents

- 1 - JVAW62 ScreenCast USB-C® Wireless Display HDMI™ Extender (1 x Transmitter & 1 x Receiver)
- 1 - USB™ Type-A extension cable (23.6")
- 1 - Quick Installation Guide (QIG)

System Requirements

- Available USB-C® port that supports DisplayPort™ Alt Mode